



NAFTA Code: FR75 T12 180W HO PH  
Equivalency Code: 180-R-110/13,2

Item Code: 32468

#### Electrical data (nominal values)

Lamp power	180 W
Supply voltage	230 V
Ballast	180 W / 230 V

#### Physical data

UVA flux (315-400 nm) $\pm 10\%$	24 W
UVA irradiance (315-400 nm) $\pm 10\%$	16 W/m <sup>2</sup>
UVB irradiance (280-315 nm) $\pm 10\%$	686 mW/m <sup>2</sup>
UVB/UVA ratio	4,3 %
Recommended useful life	800 hrs

#### Lamp specifications (acc. IEC/EN 61228)

##### a) Dimensions (in mm)

Length (nominal)	1.900,0
Length without pins (max)	1.901,3
Length base – pin (min)	1.906,0
Length base – pin (max)	1.908,4
Length with pins (max)	1.915,5
Diameter (nominal/max)	38,0 / 40,5
Base	G13 standard

b) Reflector 225°

c) Specified ballast Cosmopower S 180W/230V

##### d) Electrical data (rated values)

Lamp power	165 W
Lamp current	2.060 mA
Lamp voltage	90 V

##### e) Effective irradiance (rated values)

UV-Erythema (250-400 nm) $\pm 15\%$	110 mW/m <sup>2</sup>
nmSC (250-320 nm) $\pm 15\%$	195 mW/m <sup>2</sup>
nmSC (320-400 nm) $\pm 15\%$	15 mW/m <sup>2</sup>

f) Equivalency code 180-R-110/13,2

#### Examples of exposure times

UVA irradiance in W/m <sup>2</sup>	First session tanning time in Min.	Maximum tanning time in Min. by skin type		
		2	3	4
160	1,7	4,1	5,8	7,5
210	1,3	3,2	4,4	5,7
260	1,0	2,6	3,6	4,6
310	0,9	2,1	3,0	3,9
360	0,7	1,8	2,6	3,3

(depending on the actual UVA irradiance of the sunbed)

#### Construction elements

Mount	SM
Glass type	open
Light Colour	see picture

#### Equipment requirements

Starter	180 W / 230 V
Starter $t_{close\ min}$	
Starter $t_{close\ max}$	
Starter $U_{peak\ min}$	
Starter $U_{nonrecl\ max}$	
Cathode $I_{preheat\ min}$	
Cathode $I_{preheat\ max}$	
Operating condition $U_{L\ min}$	
Operating condition $U_{L\ max}$	
Operating condition $I_{L\ min}$	
Operating condition $I_{L\ max}$	

#### Additional specifications

This lamp is intended for sun-tanning purposes only and shall not be used in any other application

